



GLOBAL Trac adapters

The GA 100 MULTI Adapter™, designed by Nordic Aluminium, represents the latest innovation in adapter technology. There are no delays in the phase selector switch in the transition from one phase to another. The phase selector switch at the side of the adapter makes the use comfortable. Because both ends of the adapter are fitted with a locking mechanism, it can be removed directly from the track without turning it.



Adapter for all lighting tracks

MULTI Adapters are also designed to work with other manufacturers' lighting tracks. This means that the light manufacturer or fitter does not have to worry about the track on which the light will be mounted. Nordic Aluminium's three-circuit adapters include a wide selection of MULTI Adapters. The adapters come in three standard colours: grey, white and black. Adapters include several patented solutions. The materials used are halogen free and flame resistant.



Most popular adapter in the world

Our GA 69 MULTI Adapter is the world's most sold adapter. Its quality and reliability are unequalled. Product testing and 100% quality assurance are an integral part of Nordic Aluminium's strategy.



For all power supply needs


Continuous product development is essential for Nordic Aluminium. New products include a Schuko adapter. With this product the lighting track can be used for other power supply needs than lighting. It is a useful solution for meeting electricity needs in stores and small industrial premises.



3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

GA 100



Type	EAN code	Colour	PCS/ Package
GA 100-1	64100 14 530 00-6	Grey	10/100
GA 100-2	64100 14 531 00-3	Black	10/100
GA 100-3	64100 14 532 00-0	White	10/100

Truly modular adapter: end cover can be changed to allow for GAC version or trafo box installations.
 MULTI Adapter™
 - 10 A, 250 V, Safety class I
 - Max. pull strength 100 N
 - Max. torque 2.5 Nm
 - To be used with stranded wire 0.5 ...1 mm²


Slot connection. The conductors are pressed into the connectors by the cable mounting tool GB 66CT.

Type	EAN code	Colour	PCS/ Package
GA 100L-1		Grey	100/3200
GA 100L-2		Black	100/3200
GA 100L-3		White	100/3200


CG 100



GB 66CT




GAC 600



CG 100	64100 14 530 79-2	Optional cable grip	100/5000
GB 66CT	64100 14 522 51-3	Slot connection tool	1/50

GAC 600 LX



GAC600-1	64 100 14 532 92-5	Pulse control adapter	5/50
GAC600-2	64 100 14 532 93-2	Pulse control adapter	5/50
GAC600-3	64 100 14 532 94-9	Pulse control adapter	5/50


GAC 69



GAC600LX-1		Pulse control adapter, not preassembled	50
GAC600LX-2		Pulse control adapter, not preassembled	50
GAC600LX-3		Pulse control adapter, not preassembled	50

GAC 69-1		Pulse control adapter	1/50
GAC 69-2		Pulse control adapter	1/50
GAC 69-3		Pulse control adapter	1/50
GAC 69L-1		Pulse control adapter	50
GAC 69L-2		Pulse control adapter	50
GAC 69L-3		Pulse control adapter	50


GA 69



CG 69



GA 69CT




GA 69 circuit-selector adapter

Type	EAN code	Colour	PCS/ Package
GA 69-1	64100 14 530 74-7	Grey	100/4800
GA 69-2	64100 14 520 69-4	Black	100/4800
GA 69-3	64100 14 530 69-3	White	100/4800

CG 69
 GA 69CT
 MULTI Adapter™
 - 6 A, 250 V, Safety class I
 - Max. pull strength 50 N
 - Max. torque 2.5 Nm
 - To be used with stranded wire 0.5 ...1 mm²

Slot connection. The conductors are pressed into the connectors by the connector lid or by the cable mounting tool.

GAT 69




GAT 69 trafo housing adapter

Type	EAN code	Colour	PCS/ Package
GAT 69-1	64100 14 522 53-7	Grey	50
GAT 69-2	64100 14 522 54-4	Black	50
GAT 69-3	64100 14 522 55-1	White	50

MULTI Adapter™
 - 6 A, 250 V, Safety class II
 - Max. pull strength 50 N
 - Max. torque 2.5 Nm
 - To be used with stranded wire 0.5...1 mm²
 - Delivered without transformer
 - To be used only with a grounded transformer


GAT 101



GAT 101 and GAT 102 Multi Device Adapter

Type	EAN code	Colour	PCS/ Package
GAT 101-1		Grey	1/25
GAT 101-2		Black	1/25
GAT 101-3		White	1/25

GAT 102



GA 100 adapter body included.


GAT 102-1		Grey	25
GAT 102-2		Black	25
GAT 102-3		White	25

Note! To be ordered separately: GA 100 or GAC 600 adapter.

3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

GA 300



CG 100

GA 300 circuit selector adapter. Phase 2 preselected.

Type	EAN code	Colour	PCS/ Package
GA300-1	64100 14 530 43-3	Grey	10/100
GA300-2	64100 14 530 44-0	Black	10/100
GA300-3	64100 14 530 45-7	White	10/100
GA300L-1	64100 14 530 46-4	Grey	100/4800
GA300L-2	64100 14 530 47-1	Black	100/4800
GA300L-3	64100 14 530 48-8	White	100/4800

- A discreet adapter for elegant housing solutions

- For GLOBAL Trac Pro XITS and XTSF tracs

- 3 A, 250 V, Safety class I

- Max pull strength 50 N


- Max torque 2.5 Nm

- To be used with stranded wire

- Cable Grip CG 100

Slot Connection. The conductors are pressed into the connectors by the Slot Plug (included) using for example a Torx 10 screwdriver.

GA 300PP



GA 300PP adapter, plastic parts.


Type	Colour	PCS/ Package
GA300PP-1	Grey	100
GA300PP-2	Black	100
GA300PP-3	White	100

- For customized solutions

- No metal connectors

- For mechanical support only

GA 300B




Slot Plug

GA 300B Adapter body

Type	Colour	PCS/ Package
GA300B-1	Grey	100
GA300B-2	Black	100
GA300B-3	White	100

- For customized solutions

GA 300NB



Slot Plug

GA 300NB Adapter body

Type	Colour	PCS/ Package
GA300NB-1	Grey	100
GA300NB-2	Black	100
GA300NB-3	White	100

- For class II customized solutions


- No ground connector

- Without locking lever

3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

XTSA 68



XTSA 68 circuit-selector adapter

Type	EAN code	Colour	PCS/ Package
XTSA 68-1	64100 14 530 73-0	Grey	10/100
XTSA 68-2	64100 14 520 68-7	Black	10/100
XTSA 68-3	64100 14 530 68-6	White	10/100
XTSA 68L-1		Grey	100/3200
XTSA 68L-2		Black	100/3200
XTSA 68L-3		White	100/3200
CG 75	64100 14 530 77-8	Optional cable grip	100/5000

CG 75




MULTI Adapter™

- 10 A, 250 V, Safety class I
- Max. pull strength 100 N
- Max. torque 2,5 Nm
- Connecting conductors max. 3 x 1,5 mm²

Screw-in connection. The conductors are connected with screws.


XTSA 67



XTSA 67 power take-off adapter

Type	EAN code	Colour	PCS/ Package
XTSA 67-1	64100 14 500 46-7	Grey	10/100
XTSA 67-2	64100 14 520 67-0	Black	10/100
XTSA 67-3	64100 14 530 67-9	White	10/100
XTSA 67S-3	64100 14 500 44-3	Black	5/50
XTSA 67S-3	64100 14 531 67-6	White	5/50

XTSA 67S



- For GLOBAL Trac Pro tracks XTS and XTSF traces
- 16 A, 250 V/400 V, Safety class I
- Max. pull strength 100 N
- Max. torque 2,5 Nm
- Connecting conductors max. 5 x 2,5 mm²


Nipples for 3-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010), -9 aluminium.

Type	EAN code	Thread	H mm	Ø mm	Colour	Strain relief	Suitable for adapter							PCS/ Package
							GA 69	GAT 69	GA 100	GAC 600	GA 300	XTSA 68	XTSA 67	
Fixed nipple														
XTS 56/86-9	64100 14 522 56-8	M13 x 1	8.6	9.0	Aluminium	XTSA 513	x	x	x	x	x	x	x	100/500
XTS 58/8-9	64100 14 501 71-6	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	x	100/500
GA 510-1														
GA 510-1	64100 14 500 34-4		7.0	7.0	Grey	Included	x	x	x	x	x	x	x	100/500
GA 510-2	64100 14 520 86-1		7.0	7.0	Black	Included	x	x	x	x	x	x	x	100/500
GA 510-3	64100 14 530 86-0		7.0	7.0	White	Included	x	x	x	x	x	x	x	100/500
Rotating nipple *)														
XTSA 360/8-1	64100 14 500 18-4	M10 x 1	8.0	7.4	Grey	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 360/8-2	64100 14 500 19-1	M10 x 1	8.0	7.4	Black	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 360/8-3	64100 14 500 20-7	M10 x 1	8.0	7.4	White	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 360/12-1	64100 14 522 82-7	M10 x 1	12.0	7.4	Grey		x	x	x	x	x	x	x	100/500
XTSA 360/12-2	64100 14 522 83-4	M10 x 1	12.0	7.4	Black		x	x	x	x	x	x	x	100/500
XTSA 360/12-3	64100 14 522 84-1	M10 x 1	12.0	7.4	White		x	x	x	x	x	x	x	100/500
XTSA 55/12-9	64100 14 501 55-6	M13 x 1	12.0	9.0	Aluminium		x	x	x	x	x	x	x	100/500
XTSA 57/8-9														
XTSA 57/8-9	64100 14 501 59-4	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 57/8-9DD	64100 14 522 58-2	M10 x 1	8.0	6.9	Aluminium	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 57/12-9	64100 14 501 57-0	M10 x 1	12.0	7.4	Aluminium		x	x	x	x	x	x	x	100/500
XTSA 57/12-2	64100 14 520 92-2	M10 x 1	12.0	7.4	Black		x	x	x	x	x	x	x	100/500
XTSA 57/17-9	64100 14 500 37-5	M10 x 1	17.0	7.4	Aluminium		x	x	x	x	x	x	x	100/500
XTSA 57/18-9	64100 14 500 38-2	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 57/21/8-9	64100 14 500 39-2	M10 x 1	8.0	7.4	Aluminium	XTSA 510	x	x	x	x	x	x	x	100/500
XTSA 63-9	64100 14 522 59-9	M10 x 1			Aluminium		x	x	x	x	x	x	x	100/500
Nipple joint *)														
GA 37-1	64100 14 500 15-3		7.6		Grey		x	x	x	x	x	x	x	10/100
GA 37-2	64100 14 500 16-0		7.6		Black		x	x	x	x	x	x	x	10/100
GA 37-3	64100 14 500 17-7		7.6		White		x	x	x	x	x	x	x	10/100
GA 37M13-1	64100 14 500 27-6	M13 x 1	11	7.6	Grey	XTSA513	x	x	x	x	x	x	x	10/100
GA 37M13-2	64100 14 500 28-3	M13 x 1	11	7.6	Black	XTSA513	x	x	x	x	x	x	x	10/100
GA 37M13-3	64100 14 500 29-0	M13 x 1	11	7.6	White	XTSA513	x	x	x	x	x	x	x	10/100
Strain relief *)														
XTSA 510-1	64100 14 500 32-0	M10 x 1	9.0	9.2	Grey									100/500
XTSA 510-2	64100 14 520 90-8	M10 x 1	9.0	9.2	Black									100/500
XTSA 510-3	64100 14 530 90-7	M10 x 1	9.0	9.2	White									100/500
XTSA 513-1	64100 14 500 33-7	M13 x 1	9.0	9.2	Grey									100/500
XTSA 513-2	64100 14 520 91-5	M13 x 1	9.0	9.2	Black									100/500
XTSA 513-3	64100 14 530 91-4	M13 x 1	9.0	9.2	White									100/500
Thread														
GAM 10-9	64100 14 501 75-4	M10 x 1												100/500
GAM 13-9	64100 14 501 76-1	M13 x 1												100/500

*) Halogen free, VO-self-extinguishing.


Dimensions, look at the table.



3-circuit adapter accessories

Available colours: - 1 grey (RAL 7040), - 2 black (RAL 9005), - 3 white (RAL 9010).

GA 70



FIX Point™ adapter connector

Type	EAN code	Colour	PCS/Package
GA 70-1	64100 14 530 92-1	Grey	1/50
GA 70-2	64100 14 520 93-9	Black	1/50
GA 70-3	64100 14 530 93-8	White	1/50

- For GLOBAL 3-circuit adapters
- 10 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- For surface installation


GA 30



Type	EAN code	Colour	PCS/Package
GA30-1	64100 14 500 12-2	Grey	1/50
GA30-2	64100 14 500 13-9	Black	1/50
GA30-3	64100 14 500 14-6	White	1/50

- For GA300 adapter
- 3 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- For surface installation


XTSA 71



Type	EAN code	Colour	PCS/Package
XTSA 71-1	64100 14 530 97-6	Grey	1/25
XTSA 71-2	64100 14 520 96-0	Black	1/25
XTSA 71-3	64100 14 530 96-9	White	1/25

- For recessed installation with FIX Point™ GA 70
- Adjustable to different ceiling thicknesses, max. 30 mm
- For fixing hole diameters of Ø 105-125 mm

XTSK 17



Type	EAN code	Colour	PCS/Package
XTSK 17-1	64100 14 520 17-5	Grey	10/100
XTSK 17-2	64100 14 520 17-5	Black	10/100
XTSK 17-3	64100 14 530 17-4	White	10/100
XTAO 16-1	64100 14 500 49-8	Aluminium	5/50

XTAO 16



1-circuit adapters

Available colours: - 1 grey (RAL 7040), - 2 black (RAL 9005), - 3 white (RAL 9010).


GB 66 adapter

Type	EAN code	Colour	PCS/Package
GB 66-1	64100 14 509 65-1	Grey	10/100
GB 66-2	64100 14 508 66-1	Black	10/100
GB 66-3	64100 14 509 66-8	White	10/100
GB 66L-1		Grey	100/9600
GB 66L-2		Black	100/9600
GB 66L-3		White	100/9600
GB 66CT	64100 14 522 51-3	Slot connection tool	1/50


- 6 A, 250 V, Safety class I
- Max. pull strength 50 N
- Max. torque 2.5 Nm
- To be used with stranded wire 0.5 ... 1 mm²

Slot connection: The conductors are pressed into the connectors by the connector lid or by the cable mounting tool.


GB 66




GB 67



GB 67M



GB 67S



GB 67 adapter

Type	EAN code	Colour	PCS/Package
GB 67-1	64100 14 509 73-6	Grey	10/100
GB 67-2	64100 14 508 67-8	Black	10/100
GB 67-3	64100 14 509 67-5	White	10/100
GB 67L-1		Grey	100/4800
GB 67L-2		Black	100/4800
GB 67L-3		White	100/4800
GB 67M-1		Grey	100
GB 67M-2		Black	100
GB 67M-3		White	100
GB 67S-2	64100 14 500 45-0	White	1/50
GB 67S-3	64100 14 509 68-2	White	1/50

*) Cable grip CG 69 included


- 16 A, 250 V, Safety class I
- Max. pull strength 100 N
- Max. torque 2.5 Nm
- Connecting conductors max. 3 x 2.5 mm²

Screw-in connection. The conductors are connected with screws.

1-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010).

GBB 67




Type	EAN code	Colour	PCS/ Package
GBB 67-1		Grey	20/960
GBB 67-2		Black	20/960
GBB 67-3		White	20/960

- Max. pull strength 100 N
- Max. torque 2.5 Nm
- Connecting conductors max. 3 x 1.5 mm²
- Suits for use with dimmable fittings

Nipples for 1-circuit adapters

Available colours: -1 grey (RAL 7040), -2 black (RAL 9005), -3 white (RAL 9010), -9 aluminium.

Type	EAN code	Thread	H mm	Ø mm	Colour	Strain relief	Suitable for adapter		
							GB 66	GB 67	GBB 67
Fixed nipple									
XIS 56/86-9	64100 14 522 56-8	M13 x1	8.6	9.0	Aluminium	XTSA 513	x	x	100/500
XIS 58/8-9	64100 14 501 71-6	M10 x1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
GA 510-1	64100 14 500 34-4			7.0	Grey	Included	x	x	100/500
GA 510-2	64100 14 520 86-1			7.0	White	Included	x	x	100/500
GA 510-3	64100 14 530 86-0			7.0	White	Included	x	x	100/500
GB 510-1	64100 14 500 35-1			7.0	Grey	Included	x	x	100/500
GB 510-2	64100 14 508 58-6			7.0	Black	Included	x	x	100/500
GB 510-3	64100 14 509 58-3			7.0	White	Included	x	x	100/500
Rotating nipple *)									
XISA 360/8-1	64100 14 500 18-4	M10 x1	8.0	7.4	Grey	XTSA 510	x	x	100/500
XISA 360/8-2	64100 14 500 19-1	M10 x1	8.0	7.4	Black	XTSA 510	x	x	100/500
XISA 360/8-3	64100 14 500 20-7	M10 x1	8.0	7.4	White	XTSA 510	x	x	100/500
XISA 360/12-1	64100 14 522 82-7	M10 x1	12.0	7.4	Grey		x	x	100/500
XISA 360/12-2	64100 14 522 83-4	M10 x1	12.0	7.4	Black		x	x	100/500
XISA 360/12-3	64100 14 522 84-1	M10 x1	12.0	7.4	White		x	x	100/500
XISA 55/12-9	64100 14 501 55-6	M13 x1	12.0	9.0	Aluminium		x	x	100/500
XISA 57/8-9	64100 14 501 59-4	M10 x1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
XISA 57/8-9DD	64100 14 522 58-2	M10 x1	8.0	6.9	Aluminium	XTSA 510	x	x	100/500
XISA 57/12-9	64100 14 501 57-0	M10 x1	12.0	7.4	Aluminium		x	x	100/500
XISA 57/12-2	64100 14 520 92-2	M10 x1	12.0	7.4	Black		x	x	100/500
XISA 57/17-9	64100 14 500 37-5	M10 x1	17.0	7.4	Aluminium		x	x	100/500
XISA 57/18-9	64100 14 500 38-2	M10 x1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
XISA 57/18-9	64100 14 500 39-2	M10 x1	8.0	7.4	Aluminium	XTSA 510	x	x	100/500
XISA 63-9	64100 14 522 59-9	M10 x1			Aluminium		x	x	100/500
GA 57/10-1	64100 14 509 56-9	M10 x1	10.0	7.0	Grey	XTSA 510	x	x	100/500
GA 57/10-2	64100 14 508 57-9	M10 x1	10.0	7.0	Black	XTSA 510	x	x	100/500
GA 57/10-3	64100 14 509 57-6	M10 x1	10.0	7.0	White	XTSA 510	x	x	100/500
GA 57/10-9	64100 14 508 97-5	M10 x1	10.0	7.0	Aluminium	XTSA 510	x	x	100/500
GA 57/21-9	64100 14 500 29-0	M10 x1	21.0	7.0	Aluminium		x	x	100/500
Nipple joint *)									
GA37-1	64100 14 500 15-3			7.6	Grey		x	x	10/100
GA37-2	64100 14 500 16-0			7.6	Black		x	x	10/100
GA37-3	64100 14 500 17-7			7.6	White		x	x	10/100
GA37M13-1	64100 14 500 27-6	M13 x1	11	7.6	Grey	XTSA 513	x	x	10/100
GA37M13-2	64100 14 500 28-3	M13 x1	11	7.6	Black	XTSA 513	x	x	10/100
GA37M13-3	64100 14 500 29-0	M13 x1	11	7.6	White	XTSA 513	x	x	10/100
Strain relief *)									
XTSA 510-1	64100 14 500 32-0	M10 x1	9.0	9.2	Grey				100/500
XTSA 510-2	64100 14 520 90-8	M10 x1	9.0	9.2	Black				100/500
XTSA 510-3	64100 14 530 90-7	M10 x1	9.0	9.2	White				100/500
XTSA 513-1	64100 14 500 33-7	M13 x1	9.0	9.2	Grey				100/500
XTSA 513-2	64100 14 520 91-5	M13 x1	9.0	9.2	Black				100/500
XTSA 513-3	64100 14 530 91-4	M13 x1	9.0	9.2	White				100/500
Thread									
GAM 10-9	64100 14 501 75-4	M10 x1							100/500
GAM 13-9	64100 14 501 76-1	M13 x1							100/500



*) Halogen free, V0-self-extinguishing.